

**MATERIAL SAFETY DATA SHEET**1.PRODUCT IDENTIFICATION

TRADE NAME (as labeled): LATAPOXY@ 2000 Industrial Epoxy Grout Part A

CHEMICAL FAMILY:

MANUFACTURER'S NAME: MYK LATICRETE INDIA PVT. LTD.
 8-2-703/A, 4th floor Leela Gopal Towers
 Road No-12, Banjara Hills, Hyderabad – 500034
 Tel: +91 40 30413100

Reviewed & Approved by
 Dr.P.Arjunan
 Vice President – R&D

II.HAZARDOUS INGREDIENTS

CHEMICAL NAMES	CAS NUMBERS	PERCENT	ACGIH TLV	OSHA PEL	OTHER (SPECIFY)
	68953-36-6	60-70	N/A	N/A	N/A
TOFA Reaction Products with TEPA Tetraethylenepentam	112-57-2	10-14	N/A	N/A	N/A
Ine N- aminoethylpiperazien	140-31-5	3-5	N/A	N/A	N/A
*Diethylene Triamine (DETA)	000111-40-0	5-8	N/A	N/A	ACGIH TWA PPM1**
X,*Bisphenol A	000080-05-7	5-8	N/A	N/A	N/A

N/A = Not applicable or available

IX.PHYSICAL PROPERTIES

Vapour density (air =1) : N/A

Melting point or range, F: N/A

Specific gravity:0.9 –10 AT 25 C(77 F)

Boiling point or range, F: N/A

Solubility in water: Negligible to slightly soluble

Evaporation rate (buty 1 acetate =1): N/A

Vapour pressure,mmHg at 20 C: N/A

Appearance and odor: light Amber - Amine odor

HOW TO DETECT THIS SUBSTANCE (warning properties of substance as a gas, vapor, dust, or Mist):N/A.

X.REACTIVITY DATA

Stability: Stable Unstable

Conditions to avoid: N/A

Incompatibility (materials to avoid): Avoid acids oxidizing agents,halogenated organic compounds

Hazardous decomposition products (including combustion products): (from burning,heating, or reaction with other materials). Carbon monoxide, Carbon dioxide, oxides of nitrogen.

Hazardous polymerization: May occur Will not occur

Conditions to avoid: Epoxy resins or isocyanates can cause polymerization.

XI.Toxicology Information

The LD 50 for skin absorption in rabbits is 12996 mg/kg.

The oral LD 50 for rats is 21919 mg/kg

XII.Ecological Information

N/A.

XIII.Disposal Information

Dispose in compliance with local,state, and federal regulations.

XIV.Transport Information

DOT NON-BULK SHIPPING NAME: Amines,liquid, corrosive,n.o.s.(Tetraethylenepentamine/N-Aminoethylpiperazine) // 8 // UN2735 //PG 111

For material in inner packagings not over 4 liter (1 gallon) can be classified consumer commodity ORM-D.

IMO SHIPPING DATA: Amines,liquid,corrosive,n.o.s (Tetraethylenepentamine /N-Aminoethylpiperazine)//8// UN2735 //111// IMDG Page 8109-2// F.P.104 C// Placarded Corrosive // HazMat STCC = 4935601 // EMS No: 8-05 // MFAG No: 320

I IMO SHIPPING DATA: Amines,liquid,corrosive,n.o.s (Tetraethylenepentamine /N-Aminoethylpiperazine)//8// UN2735 //111// F.P.104 C// Shipment per 49 CFR 171.11

XV.Regulatory Information

All ingredients are listed on the U.S.EPA TSCA inventory of chemical substances.
Diethylene Triamine (DETA) –PA1-Pennsylvania Hazardous Substances List PA2-Pennsylvania Special Hazardous.

Substances List MA-1 Massachusetts Hazardous Substances List, MA2- Massachusetts Extraordinary Hazardous Substance List NJI-New Jersey Workplace hazardous substances List.

NJ2-New Jersey Special Health Hazards List CN-Canadian Ingredient Disclosure List NL-Not Listed.

Concentration Based Disclosure.

This product contains the following chemicals, BisphenolA, Subject to the reporting requirements of Section 313 of the Emergency Planning and Community right – to- Know Act of 1986 and of 40 CFR 372. This information must be include be included in all MSDS'S that are copies and distributed for this material. SARA Section 311 and 312 hazard classification (S) for this product are listed below: Immediate (acute) health hazard; Delayed (chronic) health hazard.

W.H.M.I.S. Code E

XVI. Other Information

This information is furnished with out warranty, representation, inducement or license of any kind; Except that it is accurate to the best of our knowledge, or obtained from sources believed by us to be Accurate.